

### Fiber Optic Video & Data Transmission for PTZ Cameras 2-Channel Composite Video + 1 Return Data

2 →

Video

#### System Design

##### Fiber Optic Video & Data Transmitter & Receiver

VOS-2010FBT/R can transmission 2-Channel digital composite video and 1 return data, the data support RS485,RS232,RS422 protocols. It is also designed for applications that require control of *PTZ cameras*.



Audio

*Stand-alone or rack-mount.* All units of VOS-2010FBT/R come in an insert card version. The cards can be inserted into our 14-slot, 19inch 4U rack-mountable card cage (VOS-CH04).

← 1

Data

*Single-Mode or Multi-Mode,* VOS-2010FBT/R only can support FC , ST Optical connector, can be used in Daisy-Chain system (Need to customize). The Transmission distance range according to the Optical Budget.




Ethernet

#### Features

- Support Point-to-Point or Daisy-Chain connection
- Uncompressed Digital Composite Video over one fiber
- Compatible with all PAL, NTSC, SECAM Video Systems
- Data support RS485(2-wire or 4-wire),RS232,RS422, Contact Closure
- Multi-mode Fiber Support for Distances up to 2.0 km
- Single-Mode Fiber Support for Distances up to 100 km
- LED Status Provide Rapid Indication of Operating Parameters
- No EMI or RFI and no ground loops
- Support Coarse Wavelength Division Multiplexing (CWDM)
- Stand alone or rack-mount
- Produce according to customer's specifications,providing OEM

#### Typical Configuration



# Fiber Optic Video & Data

## Ordering Information

Model Number		Fiber Mode	Wavelengths	Optical Power Budget	Maximum Transmission Distance
Transmitter	Receiver				
VOS-2010FBMT	VOS-2010FBMR	Multi-Mode	850nm/1310nm	16dB	2km
VOS-2010FBST	VOS-2010FBSR	Single-Mode	1310nm/1550nm	12dB	20km
VOS-2010FBST-4	VOS-2010FBSR-4	Single-Mode	1310nm/1550nm	18dB	40km
VOS-2010FBST-6	VOS-2010FBSR-6	Single-Mode	1310nm/1550nm	25dB	60km

### Note:

- The Optical Power Budget data fit Multit-mode(62.5/125  $\mu$  m),Single-Mode(9/125  $\mu$  m).
- When using 50/125  $\mu$  m multimode fiber, subtract 3 dB from the optical power budget.
- Optical transmission distance is limited to optical loss of the fiber and any additional loss introduced by connectors, splices and patch panels.
- Maximum transmission distance is also limited by fiber bandwidth.
- Power adapter is manufactured by third party and is supplied with fitted screw-terminal output cables. Power adapter included (for standalone) US, European, UK or Australian power plug.
- Please feel free to consult factory for any special requirement and customization

## Specification

<ul style="list-style-type: none"> <li>• <b>Video</b></li> </ul>	<ul style="list-style-type: none"> <li>• <b>Connectors</b></li> </ul>
Number of Channels: 2-Channel Video Input/output impedance: BNC 75 $\Omega$ Input/output Compatibility: PAL, NTSC, SECAM Input/output voltage: 1.0 Volt p-p Bandwidth: 6.5MHZ Bit Resolution: 8-Bit Digital Transmission Differential Gain: < 1.5% Differential Phase: < 1.5° Tilt: < 5% Signal-to-Noise Ratio(SNR): > 67 dB	Video: 75 $\Omega$ BNC Data: 3 Pin Terminal Block Optical: FC , ST Optional Stand-Alone Power: Screw terminal block Rack Power: AC line cord
<ul style="list-style-type: none"> <li>• <b>Data</b></li> </ul>	<ul style="list-style-type: none"> <li>• <b>Electrical &amp; Mechanical</b></li> </ul>
Data Formats: RS485(2-wire or 4-wire), RS232/422,Contact Closure Data Rate: DC to 115.2Kbps Bit Error Rate: 10E-9	Input Power Requirements: DC 5V@2A Power Adapter: AC 100V~240V Power Consumption: < 3W Stand-Alone Dimensions: 142mm $\times$ 107mm $\times$ 25mm Card for 4U Rack Dimensions: 145mm $\times$ 170mm $\times$ 20mm Shipping Weight: 1.8kg (include TX & RX)
	<ul style="list-style-type: none"> <li>• <b>Environmental</b></li> </ul>
	Operating Temperature: -45° C ~ +75° C Storage Temperature: -45° C ~ +85° C Relative Humidity: 0%~95% (non-condensing) MTBF: >100,000 hours