

Fiber Optic Video & Audio Transmitter and Receiver 1-Channel Composite Video + 2 Simplex Audio

1 → Video

System Design

Fiber Optic Video & Audio Transmitter & Receiver

VOS-1200FFT/R can transmission 1-Channel digital composite video and 2 simplex audio, ideal for Broadcast/Studio , CCTV audio and Professional AV applications. Audio transmission support single channel audio and dual channel audio --stereo audio.

2 → Audio

Stand-alone or rack-mount. All units of VOS-1200FFT/R come in an insert card version. The cards can be inserted into our 14-slot, 19inch 2U rack-mountable card cage (VOS-CH02).

Data

Single-Mode or Multi-Mode, VOS-1200FFT/R only can support FC /PC Optical connector, can be used in Daisy-Chain system (Need to customize). The Transmission distance range according to the Optical Budget.


Ethernet

Features

- Support Point-to-Point or Daisy-Chain connection
- Uncompressed Digital Composite Video over one fiber
- 24-Bit Digitally Encoded Audio over one Fiber
- Compatible with all PAL, NTSC, SECAM Video Systems
- Multi-mode Fiber Support for Distances up to 2.0 km
- Single-Mode Fiber Support for Distances up to 100 km
- LED Status Provide Rapid Indication of Operating Parameters
- No EMI or RFI and no ground loops
- Support Coarse Wavelength Division Multiplexing (CWDM)
- Stand alone or rack-mount
- Produce according to customer's specifications ,providing OEM



Typical Configuration



Fiber Optic Video & Audio

Ordering Information

Model Number		Fiber Mode	Wavelengths	Optical Power Budget	Maximum Transmission Distance
Transmitter	Receiver				
VOS-1200FFMT	VOS-1200FFMR	Multi-Mode	1310nm	16dB	2km
VOS-1200FFST	VOS-1200FFSR	Single-Mode	1310nm	12dB	20km
VOS-1200FFST-4	VOS-1200FFSR-4	Single-Mode	1310nm	18dB	40km
VOS-1200FFST-6	VOS-1200FFSR-6	Single-Mode	1550nm	25dB	60km

Note:

- The Optical Power Budget data fit Multi-mode(62.5/125 μ m), Single-Mode(9/125 μ m).
- When using 50/125 μ m multimode fiber, subtract 3 dB from the optical power budget.
- Optical transmission distance is limited to optical loss of the fiber and any additional loss introduced by connectors, splices and patch panels.
- Maximum transmission distance is also limited by fiber bandwidth.
- Power adapter is manufactured by third party and is supplied with fitted screw-terminal output cables. Power adapter included (for standalone) US, European, UK or Australian power plug.
- Please feel free to consult factory for any special requirement and customization

Specification

<ul style="list-style-type: none"> • Video 	<ul style="list-style-type: none"> • Connectors
<ul style="list-style-type: none"> Number of Channels: 1-Channel Video Input/output impedance: BNC 75 Ω Input/output Compatibility: PAL, NTSC, SECAM Input/output voltage: 1.0 Volt p-p Bandwidth: 6.5MHz Bit Resolution: 8-Bit Digital Transmission Differential Gain: < 1.5% Differential Phase: < 1.5° Tilt: < 5% Signal-to-Noise Ratio(SNR): > 67 dB 	<ul style="list-style-type: none"> Video: 75 Ω BNC Audio: RJ-45 or Terminal Block Optical: FC (standard) Stand-Alone Power: Screw terminal block Rack Power: AC line cord
<ul style="list-style-type: none"> • Audio 	<ul style="list-style-type: none"> • Electrical & Mechanical
<ul style="list-style-type: none"> Number of Channels: 2-Channel Simplex Audio Audio input/output Level: 6 dBm Audio in/output impedance: 600 Ω Bandwidth: 10Hz ~ 20KHz Bit Resolution: 24-Bit Signal-to-Noise Ratio(SNR): > 80 dB 	<ul style="list-style-type: none"> Input Power Requirements: DC 5V@2A Power Adapter: AC 100V ~ 240V Power Consumption: < 3W Stand-Alone Dimensions: 95mm \times 70mm \times 25mm Card for 2U Rack Dimensions: 95mm \times 70mm \times 25mm Card for 4U Rack Dimensions: 145mm \times 170mm \times 20mm Shipping Weight: 1.2kg (include TX & RX)
	<ul style="list-style-type: none"> • Environmental
	<ul style="list-style-type: none"> Operating Temperature: -45° C ~ +75° C Storage Temperature: -45° C ~ +85° C Relative Humidity: 0% ~ 95% (non-condensing) MTBF: >100,000 hours